

California Climate Zones																
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
2019 CA T24 U-Factors	0.048	0.048	0.048	0.048	0.048	0.048	0.065	0.065	0.065	0.048	0.048	0.048	0.048	0.048	0.048	0.048

Warm Temperature Test Range 50-100 degs F, 70 degs F average																
BamCore Prime Wall -	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047	0.047
Out Performance	0.001	0.001	0.001	0.001	0.001	0.001	0.018	0.018	0.018	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Ridged Foam Needed	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No

Conventional 2x6	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082	0.082
Under Performance	-0.034	-0.034	-0.034	-0.034	-0.034	-0.034	-0.017	-0.017	-0.017	-0.034	-0.034	-0.034	-0.034	-0.034	-0.034	-0.034
Ridged Foam Needed	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Cold Temperature Test Range 0 - 70 degs F, 35 degs F average																
BamCore Prime Wall -	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037	0.037
Out Performance	0.011	0.011	0.011	0.011	0.011	0.011	0.028	0.028	0.028	0.011	0.011	0.011	0.011	0.011	0.011	0.011
Ridged Foam Needed	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No

Conventional 2x6	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069	0.069
Under Performance	-0.021	-0.021	-0.021	-0.021	-0.021	-0.021	-0.004	-0.004	-0.004	-0.021	-0.021	-0.021	-0.021	-0.021	-0.021	-0.021
Ridged Foam Needed	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes